

B**B3300SU****Kubota****SPECIFICATIONS****Specifications**

Model			B3300SU
Engine			
Type			E-TVCS, liquid cooled, 4-cylinder diesel
Make, Model			Kubota V1505-E3-D24H
PTO horsepower	HP (kW)		25.0 (18.6)
Engine gross horsepower	HP (kW)		33.0 (24.6)
Rated RPM	rpm		2700
Bore and stroke	in. (mm)		3.1 × 3.1 (78 × 78.4)
Displacement	cu. in. (cc)		91.4 (1498)
Air cleaner			Dual paper element
Lubrication			Forced lubrication
Cooling system			Pressurized radiator
Radiator fan			Radial air flow
Capacities			
Fuel tank	gal (ℓ)		8.1 (31)
Cooling system	qts. (ℓ)		4.7 (4.5)
Engine oil	qts. (ℓ)		5.7 (5.4)
Transmission case	gal (ℓ)		3.83 (14.5)
Drive train			
Clutch			Dry single plate
Transmission			HST (3 ranges)
Differential lock			Standard
Final drive			Spur gear
Brake			Multi-plate wet disc
PTO			
Type			Live
Rear	rpm		540
Mid	rpm		N/A
Hydraulics			
Type			Open center
Pump			Dual pump
Total pump output	gpm (ℓ/min.)		9.9 (37.5)
Hydraulic outlet			Front outlet (w/ standard valve)
3-point hitch			Category I
Hydraulic control system			Quarter inching valve
Lift capacity	at lift point	lbs. (kg)	1786 (810)
	24" behind LP	lbs. (kg)	1400 (635)
Steering			Power steering
Tire size			
Front			R1: 7-12/R4: 25 x 8.5-14
Rear			R1: 12.4-16/R4: 15-19.5
Traveling speeds (at rated engine rpm)			
Forward	mph (km/h)		R1: 11.9 (19.1)/R4: 12.8 (20.6)
Reverse	mph (km/h)		R1: 9.5 (15.3)/R4: 10.2 (16.5)
Dimensions			
Overall length (w/o 3P)	in. (mm)		99.2 (2520)
Overall width (min. tread)	in. (mm)		R1: 53.7 (1365)/R4: 57.9 (1470)
Wheelbase	in. (mm)		66.8 (1696)
Ground clearance	in. (mm)		R1: 14.6 (370)/R4: 15.6 (395)
Turning radius with brake	feet (m)		7.9 (2.4)
Weight	lbs. (kg)		R1: 1764 (800)/R4: 1929 (875)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

