

RTV

RTV900XT

SPECIFICATIONS

Specifications

Model		RTV900XT General Purpose		RTV900XT Worksite		RTV900XT Utility		
Body color		Orange		Orange	Orange with S package	Camouflage	Orange	
Engine	Make	KUBOTA D902-E3-UV						
	Type	3-cylinders, 4-cycle, diesel, OHV						
	Displacement	cu.in (cc)	54.8 (898)					
	Horsepower	HP (kW)/rpm	21.6 (16.1)@3200					
Fuel tank capacity		U.S.gals (ℓ)	7.4 (28)					
Transmission		Variable hydro transmission (VHT Plus 2)						
Max. traveling speed		mph (km/h)	25 (40)					
Wheels, drive system		4, Rear 2WD or 4WD						
Differential lock		Standard; foot operated with mechanical holder						
Gear selection		Hi-Med-Lo range forward, neutral, reverse						
Brakes	Front / Rear	Wet-disc brakes						
	Parking brake	Rear wheel, hand lever						
Steering		Hydrostatic power						
Suspension		Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers						
Dimensions	Length	in. (mm)	117.7 (2990)	119.3 (3030)				
	Width	in. (mm)	59.8 (1520)					
	Height, overall	in. (mm)	79.1 (2010)					
	Front tread centers	in. (mm)	45.3 (1150) w/HDWS & ATV, 46.5 (1180) w/Turf					
	Rear tread centers	in. (mm)	46.5 (1180) w/HDWS & ATV, 47.6 (1210) w/Turf					
	Wheelbase	in. (mm)	77.4 (1965)					
	Ground clearance front/rear axle	in. (mm)	8.3 (210) / 7.5 (190)					
	Turning diameter	ft. (m)	25.6 (7.8)					
Max. rolling weight (Towing capacity)		lbs. (kg)	1300 (590)					
Payload capacity		lbs. (kg)	1697 (770)	1642 (745)	1653 (750)	1576 (715) w/HDWS, 1565 (710) w/Turf		
Weight		lbs. (kg)	1874 (850)	1929 (875)	1918 (870)	1995 (905) w/HDWS, 2006 (910) w/Turf		
Cargo bed	Width × Length × Depth	in. (mm)	52 (1320) × 46.7 (1180) × 11.4 (290)					
	Volume	cu ft. (m ³)	16 (0.455)					
	Bed height (unloaded)	in. (mm)	31.5 (800)					
	Cargo bed load	lbs. (kg)	1102 (500)					
Sound level, operator ear		db. (A)	87 @ Max. engine speed w/ no load					89 @ Max. engine speed w/ no load
Tires	Front	25×10–12 ATV, 6PLY	25×10–12 ATV, 6PLY				—	
		25×10–12 HDWS, 6PLY	25×10–12 HDWS, 6PLY				25×10–12 HDWS, 6PLY	
		25×12–12 Turf, 4PLY	—				25×12–12 Turf, 4PLY	
	Rear	25×11–12 ATV, 6PLY	25×11–12 ATV, 6PLY				—	
		25×10–12 HDWS, 6PLY	25×10–12 HDWS, 6PLY				25×10–12 HDWS, 6PLY	
		25×12–12 Turf, 4PLY	—				25×12–12 Turf, 4PLY	
Alloy wheel (not available with Turf tire)		Opt.	Opt.	Std.	Opt.	Opt.		
Front guard		Opt.	Std.	Std.	Std.	Std.		
Hydraulic bed lift		Opt.	Std.	Std.	Std.	Std.		
Hydraulic Utility Valve		—	—	—	—	Std.		
Speedometer		Opt.	Opt.	Std.	Std.	Std.		
Spray-on Bed Liner		—	Opt.	Std.	Opt.	—		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.