

RTV-X Series

Specifications

RTV-X1120D



Model			RTV-X1120D	
Body color			Kubota Orange	Realtree AP Camo
Engine			KUBOTA D1105-E4-UV	KUBOTA D1105-E4-UV
Make			KUBOTA D1105-E4-UV	
Type			3-cylinders, 4-cycle, diesel, OHV	
Displacement			68.5 (1123) cu.in (cc)	68.5 (1123)
Horsepower			24.8 (18.5) @3000 HP (kW)/rpm	24.8 (18.5) @3000
Cooling system			Liquid	
Battery			650 CCA	
Transmission			Variable hydro transmission (VHT-X)	Variable hydro transmission (VHT-X)
Gear selection			Hi-Lo range forward, neutral, reverse	
Max. traveling speed			0-29 (0-46.4) mph (km/h)	
4WD system			Limited-slip differential	
Front differential			Limited-slip differential	
Rear differential			Foot operated differential lock	
Steering			Hydrostatic power	
Brakes			Wet-disc brakes	
Front / Rear			Wet-disc brakes	
Parking brake			Rear wheel, hand operated	
Suspension			Independent, Dual A-arms with adjustable spring preload	
Front suspension			Independent, Dual A-arms with adjustable spring preload	
Front suspension travel			8 (205) in. (mm)	
Rear suspension			Independent with coil over shock	
Rear suspension travel			8 (205) in. (mm)	
Headlights			Two 37.5 watt blue-tint halogen, optical axis adjustment	Two 37.6 watt blue-tint halogen, optical axis adjustment
Occupant Protective System (OPS)			2.0 (50.8) steel tube	
Tubular overhead structure			2.0 (50.8) steel tube	
Seat belts			3-point	
Certification			SAE J2194 and OSHA 1928 ROPS and ANSI B71.9	
Dimensions			122.5 (3110) in. (mm)	
Length			122.5 (3110)	
Width			63.2 (1605) in. (mm)	
Height, overall			79.5 (2020) in. (mm)	
Front tread centers			48.8 (1240) in. (mm)	
Rear tread centers			48.8 (1240) in. (mm)	
Wheelbase			80.5 (2045) in. (mm)	
Turning radius			13.1 (4.0) ft. (m)	
Weight			2061 (935) lbs. (kg)	
Towing capacity			1300 (590) lbs. (kg)	
Payload capacity			1510 (685) lbs. (kg)	
Ground clearance			10.5 (266) in. (mm)	
Front			10.5 (266)	
Rear			10.4 (263) in. (mm)	
Under foot platform			11.0 (280) in. (mm)	
Cargo bed			Steel	
Material			Steel	
Width x Length x Depth			57.7 (1465) x 40.5 (1030) x 11.2 (285) in. (mm)	
Volume			15.2 (0.43) cu ft. (m3)	
Bed height (unloaded)			34.9 (887) in. (mm)	
Cargo bed load			1102 (500) lbs. (kg)	
Dump			Hydro power lift	
Fuel tank capacity			7.9 (30) U.S. gals (L)	
Sound rating at operator's ear			84 dB. (A)	
Tires			25x10-12, 6PLY	
Front and Rear			25x10-12, 6PLY	
ATV			25x10-12, 6PLY	
HDWS			25x10-12, 6PLY	
TURF			—	
Front guard design			Center, bumper and lens	
Alloy wheel (not available with Turf tire)			Std.	
Hydraulic bed lift			Std.	
Spray-on Bed Liner			Opt.	

*New SAE J1940

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.